Link do produktu: https://www.lotart.pl/flyer-truck-c250-350-electro-p-141.html

Flyer-Truck C250-350 electro



Opis produktu

| Engine / | AC Electric engine 2 piece per 80V, 12.5 kW, Total 25 kW / 34 HP |
|--------------------|--|
| and by stem | Kir, rotar 25 kir, 5 mil |
| | S2 / IP54 / IP20 |
| | single gear PMS |
| Control | Inverter steering ACE 80V |
| system | |
| Truck specifi | Speed: ca. 23 km/h (14 m/h) |
| cations | |
| | Range: ca. 80 km (50 miles) |
| | power regulation through |
| | foot pedal |
| | Operations: joystick operations for landing gear bracket |
| | Transmission: 2 wheel drive |
| | Steering: electric hydraulic steering operated by steering wheel |
| Weight | max. weight: 10.455 kg |
| | Truck empty weight: 5.855 kg |
| | Pick up weight max.: 4.600 kg |
| Batteries | Lead acid batteries, 10 pieces 500 Ah |
| Battery charger | 400/80 V - 80/95 A integrated |
| Brake | Hydraulic oil-multi-disc brake, low-wear in |
| brake | , |
| | the drive gear 6200 Nm, |
| | parking brake electromagnetic brake 6200 |
| | Nm |
| Tire | Drive wheels rear: 225/75 R10 16PR |
| iire | Drive wheels rear: 225/75 KTO 16PR |

| | Steering wheel front: 6.90/6.00-9 |
|--------------|---|
| Cabin | Driver cabin for one operator with |
| | ergonomically situated operating |
| | elements, side door, sliding window |
| Landing | Universal receptacle for double front |
| gear bracket | landing gear, up to width tire 800 mm, with |
| | hydraulic front gear wheel hold system, |
| | hydraulic door closing system |
| Equipment | Driver, movable working and safety lights |
| | Safety up turn light on top |
| | Windshield wipers in the front with |
| | wash |
| | ∘ Signal horn |
| | Fire-extinguisher |